



CRANES & COMPONENTS

Reference: 111403

Denomination: 40 Ton foot mounted hoist GHF, H.O.L. 11 m +

Year: 2018

Owner

Owner: WF STEEL & CRANE LTD.

Address: Head Office 2107-6th Street

Country: Canada

City: Nisku, AB T9E 7X8

Hoist Characteristics

Type GHF	Motor GHF-210	Brake c.c.(90v)	
Wire rope (mm) 22	Drum ø (mm) 404	Capacity (Tn) 40	r.p.m. 3600/600
Length (m) 53,5	Drum length (mm) 1400	Falls 4/1	Working Group M4
Power (kw) 34,5/5,15	Gear box Polipasto	Hook 12	Hook path (m) 11
Sheave ø 450	Speed (m/min) 4,8/0,8	Type of Hook Simple	Compensation pulley ø 450

Cross Travel Characteristics

Type Testero para carro (patas)	Motor VC-85	Gear box RFS250-3T	
Wheel ø (mm) 250	Number of engines 2	r.p.m. 3600 Vari.	Working Group M4
Speed (m/min) 20	Power (kw) 1,8	Distance between wheels 1800	

Long Travel Characteristics

Type Testeros Apoyado Birrail	Motor VC-110	Gear box RFS315-3T	
Wheel ø (mm) 315	Number of engines 4	r.p.m. 3600 Vari.	Wheel opening (mm) 80
Working Group M4	Span (m) 16.000	Power (kw) 2,8	Speed (m/min) 30
Structure Working Group A4	Distance between wheels 4x1800		

Slewing Movement Characteristics

Number of engines 0	Motor voltage (V/Hz) 400/50
----------------------------	------------------------------------

Reel Drum

Energy Supply

Energy supply (v) 460	Location Interior	Frequency (Hz) 60
Electric controls No	Controls (v) 120	